

Intellian® i2

Compact and Smart Marine Satellite TV Antenna System



HDTV
COMPATIBLE

A firm hold on the signal

Dynamic Beam Tilting (DBT) uses a high performance, constantly adjusting sub-reflector which allows the antenna to remain relatively still, eliminating the constant whine of stepper motors while providing clear reception while the boat is in motion.

Faster signal acquisition

Intellian's exclusive Wide Range Search (WRS) algorithm allows antenna to search, find and lock on to a signal with incredible speed and accuracy.

Compact size

33cm antenna reflector diameter with an antenna weighs less than 4.5kg.

Simple & Easy installation

With just a single cable to connect the antenna and the ACU, Intellian i2 systems are quick and easy to install. Our advanced ACU is designed to require a minimum of set-up so you can begin to enjoy TV programs aboard your boat in no time.

Performance & Value

All these benefits are yours to enjoy without having to worry about a hefty price tag. Our goal is to provide an affordable, high value system so you can enjoy big- ticket broadcast entertainment and not have to worry about the price of admission.

Intellian

Connect with the best


Intellian® i2

Compact and Smart Marine Satellite TV Antenna System


Technical Specifications

Physical	
Radome Height	38cm / 15"
Radome Diameter	37cm / 14.6"
Reflector Diameter	33cm / 13"
Weight	4.5kg / 9.5lbs
Environmental	
Operating Temp. Range	-25°C to +55°C / -13°F to +131°F
Storage Temp. Range	-40°C to +80°C / -40°F to +176°F
Water Ingress	IPX6
Approvals	CE/FCC
Warranty	3 year parts and 1 year labor
Performance	
Reception Frequency	Ku-band (10.7~12.75GHz)
Polarization	Vertical / Horizontal
Minimum EIRP	51dBW
Azimuth Range	680°
Elevation Range	10° to 80°
Ship's Motion	Roll ±25°, Pitch ±15°
Roll & Pitch Response Rate	60° / sec
Turning Rate	60° / sec
RF Output	Dual Output
Antenna Control Unit	
Dimensions (WxDxH)	17.8cm x 21.7cm x 5.4cm / 7" x 8.5" x 2.1"
Weight	1.2kg / 2.6lbs
Display	2 line 20 character VFD module
GPS Interface	Built-in (NMEA 0183 GPS)
Power Requirement	9.0~30.0V DC
Power Consumption	Typ. 30W, Max. 50W

System Diagram



System Dimension



Key Features

- Travel further north or south with extended elevation range 10° to 80°
- Stay locked on in rough seas, 60° per second turning rate
- Compatible with global satellite TV service providers
- Smaller size with bigger performance
- Simplicity of design, no fragile compass and no rate sensor
- Switch channels as fast as you do at home

Global HQ
Innovation Center/Factory
Intellian Technologies, Inc
T +82 2 511 2244
F +82 2 511 2235

APAC
Seoul Office
Intellian Technologies, Inc.
T +82 2 511 2244
F +82 2 511 2235

Americas HQ
Irvine Office
Intellian Technologies USA, Inc.
T +1 949 727 4498
F +1 949 271 4183
Toll Free +1 888-201-9223

South America
Rio de Janeiro Office
Intellian do Brasil Tecnologia Ltda.
T +55 21 3176 2048
F +55 21 9612 1431

EMEA HQ
Rotterdam Office
Intellian B.V.
T +31 1 0820 8655
F +31 1 0820 8656

EMEA
Southampton Office
Intellian Ltd.
T +44 2380 019 021
F +44 2380 767 092



©2014 Intellian Technologies, Inc. All rights reserved. Intellian and the Intellian logo are registered trademarks. DBT, WRS, i2 and i-Series are trademarks of Intellian Technologies, Inc. in the U.S. and/or various countries. All other trademarks are the property of their respective owners. Information in this document is subject to change without notice. ISO9001 / ISO14001 Certified Intellian has more offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Intellian Website at intelliantech.com