

# **HARKEN®**

## **INSTRUCTION SHEET**

### **Carbo Block U-Lock**

**40 mm (H-27808A), 57 mm (H-56798),  
75 mm (H-29934B)**

N15W24983 Bluemound Rd. • Pewaukee, WI 53072 U.S.A.  
Telephone: (262) 691-3320 • Fax: (262) 701-5780  
Web: [www.harken.com](http://www.harken.com) • Email: [harken@harken.com](mailto:harken@harken.com)

To change headpost lock  
from front to side position,  
remove shackle, turn post  
and re-install shackle.

Remove U-lock to let  
block swivel freely.



## Maintenance

Keep your equipment clean and free-running by frequently flushing with fresh water. Periodically clean with mild detergent and water solution. Spin sheaves to distribute soap solution evenly. Flush with fresh water.

In corrosive atmospheres, stainless parts may show discoloration around holes, rivets and screws. This is not serious and may be removed with a fine abrasive.

**IMPORTANT! Exposure to some teak cleaners and other caustic solutions can result in discoloration of part and is not covered under the Harken warranty.**

## Warranty

For additional safety, maintenance and warranty information see [www.harken.com/manuals](http://www.harken.com/manuals) or the Harken® catalog.

Printed in USA. 4875 02/14