

225° MASTHEAD LIGHT w. DECK LIGHT, SINGLE, VERTICALLY MOUNTED

3 nautical miles	201-011DLX (12m – 20m / 39.4' - 65.6'')
5 nautical miles	301-011DLX (20m – 50m / 65.6' – 164')

This LED navigation light consists of two high-power LEDs that produces light in the specified angle utilizing special designed PMMA light guides.

A deck light unit is mounted under the masthead unit to provide a comfortable light on deck.

The precision machined 6082 aluminium housing with an anodized surface makes the light a rugged and durable housing for the LEDs and electronics contained within.

The interior is completely filled with a special potting resin making it water- and vibration proof.

Produced in our in-house manufacturing facility to meet and exceed exacting standards such as EN14744 and UL1104, under a quality management system continuously surveyed by Lloyds Register Quality Assurance.

Each light is subjected to final testing for a minimum of 16 hours of continuous operation bringing the total test time beyond 24 hours.

This navigation light is in compliance with the following standards:

- COLREG72
- EN14744
- IEC 60945
- USCG (UL1104)

Together with an appropriate Control & Monitoring System, such as Lopoliht's own NLC* this navigation light can form part of an IMO MSC 253(83), LY3 and LY4 compliant system.

*) information found here: www.lopolight.com/NlcPanel



Technical specifications**201-011;**

Vessel size: 12m – 20m (39.4' – 65.6')

Visibility: >3 nautical miles

Intensity: >15cd

Power consumption: 5 Watt; Current: 0,41A @12 VDC - 0,2A @24 VDC

301-011;

Vessel size: 20m – 50m (65.6' – 164')

Visibility: >5 nautical miles

Intensity: >65cd

Power consumption: 8,5 Watt; Current: 0,71A @12 VDC - 0,35A @24 VDC

Light colour: **White**

Deck light;

Vessel size: **All vessel sizes**

Intensity: **1500lumen**

Lens options: **6°, 26°, 36°, 74°**

Power consumption: **6 Watt; Current: 0,50A @12 VDC - 0,25A @24 VDC**

Light colour: **White (3500 Kelvin)**

Operating voltage: **10 - 32 VDC**

Number of LEDs:

Masthead: **2**

Deck light: **3**

Operating temperature: **-25°C to +55°C**

IP rating: **IP68**

Mounting: **Vertical**

Connection: **1 cable consisting of 4 x 0,5 mm² leads, a screen and insulation.**

- **Red lead = Masthead power**
- **Black lead = Masthead GND**
- **White lead = Deck light power**
- **Green lead = Deck light GND**

Certification: **Pending**

The product is in compliance with the following standard(s):

COLREG72/ EN14744 / IEC 60945 / USCG (UL1104)

Dimensions: **See drawing**

Weight: **1,2kg**

Warranty:

Lopolight products are covered by a 5-year limited warranty.

Warranty conditions can be found on www.lopolight.com/Home/Service







Included in package:

- 1 pc. Navigation light w. deck light, pre-cabled with 15m marine grade cable
- 4 pcs. Mounting screws (M6 x 8 mm)
- Installation instructions

Ordering information

VISIBILITY	CABLE LENGTH	PART NUMBER SILVER FINISH	PART NUMBER BLACK FINISH
3 nautical miles	15m / 49,1' (standard)	201-011DLX	201-011DLX-B

5 Nautical miles	15m / 49,1' (standard)	301-011DLX	301-011DLX-B
------------------	------------------------	------------	--------------



Mounting hole
Ø6,20

Pre-wired Cable Exit Ø5,5mm shielded
marine cable

201-011DLX 3nm masthead Vertical Mount with Deck Light

DRAWING NO.: 201-011AE	REV. NO.: 0	SIZE: A3	DRAWN BY: Sergio
SCALE: 1:1	TOLERANCES: DS/ISO 2768-f	REVIEWED BY: PHC	CREATION DATE: 04-10-2018
MATERIAL DESCRIPTION: Aluminium, Acrylic			

(20µ) Silver anodized according to EN ISO 7599
(50µ) Black anodized according to MIL-A 8625F
This Drawing, and the information within, is the property of Lopolight ApS and may not be used in any form without express permission there from. Lopolight reserves the right to change this drawing and assumes no liability for the information communicated herein. Use of dimensions and other information in this drawing is at the users own risk.



Lopolight ApS
Bakkegaardsvej 513
DK-3050, Humlebaek
Denmark

Tel:(+45) 32 48 50 30 Fax:(+45) 32 48 50 32
info@lopolight.com

White 225°

CL

50MM AT A3