

## SPC10T/SPC15T/SPC30T 70/25V Weather Resistant PA Horn Speakers

Thank you for your choice of one of Speco Technologies' **SPC10T/SPC15T/SPC30T** PA Horn Speakers. This unit is designed and manufactured to provide a sturdy option for sound projection in loud or long-distance environments. The durable, weatherproof construction ensures long-life outdoors, but the unit is well-suited for indoor use.

## **INSTALLATION INSTRUCTIONS:**

- 1) The **SPC10T/SPC15T/SPC30T** is constructed with a pivoting, metal mounting bracket.
- 2) Loosen the screws connecting the bracket to the horn, and remove the bracket.
- 3) The mounting bracket contains 2 holes for screws. Use screws with greater than 3/8" diameter head to ensure safe installation. Screw the bracket to the mounting surface where you wish to install the horn.
- 4) Reattach the bracket to the horn, rotate the horn to your desired angle and tighten the screws securely.
- 5) On the rear of the horn is a selectable 70/25V transformer. Using the chart printed above the transformer screw, turn the screw to the desired power rating and voltage setting. TAKE PRECAUTION THAT THE POWER YOU SELECT, IN COMBINATION WITH OTHER SPEAKERS, DOES NOT EXCEED 80% OF RATED POWER OF YOUR AMPLIFIER. Please consult Speco Technologies Technical Support if you are not familiar with this concept.
- 6) To aid weather-proofing, the wire connections are sealed internally, and accessible through a 2' lead.
- 7) Connect the White (positive) & Black (negative) wires to the corresponding outputs on your amplifier.
- 8) The green/yellow ground wire should also be connected to the building structure or grounding apparatus.

## **SPECIFICATIONS:**

- Frequency Response: 315Hz (SPC10T)/280Hz (SPC15T)/250Hz(SPC30T) ~ 20kHz
- Max Power: 20W (SPC10T)/30W(SPC15T)/60W(SPC30T)
- Impedance: 8 Ohms
- Weatherproof Aluminum construction

## WARRANTY INFORMATION:

We warranty this product to be free from any manufacturing or material defects for two (2) years from the date of purchase.

This warranty will not extend to any products which have been subjected to misuse, neglect, accident, or improper installation, used in violation of instructions furnished by us; or to units which have been repaired or altered outside of the factory. This limited warranty does not apply to broken cases, batteries, or other physically damaged parts. If a Speco Technologies product is purchased from an unauthorized distributor or other source, including RETAILERS, MAIL ORDER SELLERS and ONLINE SELLERS, it will not be honored or serviced under existing Speco Technologies warranty policy. Any sale of products by an unauthorized source or other manner not authorized by Speco Technologies will void the warranty on the applicable product.

Upon request by customer, Speco Technologies ("The Company") will, at customer's expense, repackage merchandise in new cartons, replace missing accessories, and return in resalable condition. Unless requested, the company will replace and return all merchandise in the packaging in which it was received. This warranty is in lieu of all expressed warranties, expressed or implied, and of all obligations or liability on our part, and we neither assume nor authorize any representative or other person to assume for us any obligation or liability. In no event shall we be liable for incidental or consequential damages arising from the use of the product, or for any delay in the use of this product due to causes beyond our control. Some states do not allow limitations of how long an implied warranty lasts and/or do not allow the exclusion or limitation of consequential damages. The above limitations on implied warranty and consequential damages may not apply to you. This warranty gives you specific legal rights. You may have other rights which vary from state to state. This limited warranty extends to products listed in the company's current price schedule.

Speco Technologies is constantly developing and improving products.

We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Speco Technologies . 200 New Highway . Amityville . NY . 11701 . www.specotech.com