



5nm 225° Masthead + 6W decklight, silver anodized, with 15m cable

301-011DLX 15M

5nm masthead+6W decklight, silver anodized
Vertical mounted with 15m cable

Specifications	
Number	301-011DLX 15M
Light Color	White
Dimensions metric	54 x 38,7 x 72,2
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>52cd
Dimensions imperial	2.1" x 1.5" x 2.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	5nm
Included In Package	1 Navigation light,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438013056
IP rating	IP68
Power draw (W)	4,1
UPC Code	879343013059
Connection	15m cable

Specifications	
Current consumption (mA @ 12VDC)	320
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	170
Vessel size	20-50M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	1.46 Kg
Weight (Oz)	51.49 Oz