



5nm 225° Masthead, double, vertical mount, with 0,7m cable

301-011ST

5nm Double Masthead, vertical mounted
Silver anodized, with 2 x 0,7m cable

Specifications	
Number	301-011ST
Light Color	White
Dimensions metric	92,5 x 88,6 x 85
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>52cd
Dimensions imperial	3.6" x 3.4" x 3.3"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	5nm
Included In Package	1 Navigation light, precabled with 0.75 meter shielded marine grade cable, 2 Mounting screws (M6 * 8 mm), Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438013124
IP rating	IP68
Power draw (W)	4,1
UPC Code	879343013127
Connection	0.7m cable

Specifications	
Current consumption (mA @ 12VDC)	320
Stock status	Made to order
Current consumption (mA @ 24VDC)	170
Vessel size	20-50M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	1 Kg
Weight (Oz)	35.27 Oz