



# SEALING & BONDING | COMPETITOR COMPARISON

SIKA TECHNOLOGY	COMPETITORS		SIKA ADVANTAGES	SIKA APPLICATIONS
POLYURETHANE	BOATLIFE	3M		
<b>Sikaflex®-290 DC</b>	Teak Deck Sealant*	N/A	<ul style="list-style-type: none"> <li>■ UV Stable</li> <li>■ Resistant to typical cleaning agents</li> </ul>	<ul style="list-style-type: none"> <li>■ Deck seam sealing</li> </ul>
<b>Sikaflex®-291 LOT</b>	Life Calk*	4200	<ul style="list-style-type: none"> <li>■ Long open time (2-4) hours for projects that require slower product</li> <li>■ Greater flexibility (+/- 25% joint movement)</li> <li>■ Paintable/sandable</li> <li>■ Adheres to self for easy repair</li> <li>■ Easy to tool</li> </ul>	<ul style="list-style-type: none"> <li>■ Thru-hull</li> <li>■ Keel joints</li> <li>■ Hatches</li> <li>■ Rub rails and vents</li> <li>■ Hull seams</li> <li>■ Bedding and sealing deck hardware</li> </ul>
<b>Sikaflex®-291</b>	Life Calk*	4200 FS	<ul style="list-style-type: none"> <li>■ 30-60 minute tack-free</li> <li>■ Excellent sag resistance on large bead</li> <li>■ Good above or below waterline</li> <li>■ Paintable/sandable</li> <li>■ Adheres to self for easy repair</li> <li>■ Easy to tool</li> </ul>	<ul style="list-style-type: none"> <li>■ Bedding and sealing deck hardware</li> </ul>
<b>Sikaflex®-292</b>	N/A	5200 & 5200 FS	<ul style="list-style-type: none"> <li>■ Non-sag for overhead or large vertical surfaces</li> <li>■ Clamping or fasteners often not needed</li> <li>■ Excellent green strength for initial bonding</li> <li>■ 30-minute tack-free</li> <li>■ Paintable/sandable</li> </ul>	<ul style="list-style-type: none"> <li>■ Deck-to-hull</li> <li>■ Stringers</li> <li>■ Struts and supports</li> <li>■ Transoms</li> <li>■ Radar mounts</li> <li>■ Chain plates and internal finishings</li> </ul>
<b>Sikaflex®-295UV</b>	Life Seal (Hybrid)	4000 UV**	<ul style="list-style-type: none"> <li>■ Permanently seals and bonds acrylic and polycarbonate</li> <li>■ Available in black or white for UV stable sealing</li> <li>■ Non-yellowing</li> <li>■ Easy to use</li> </ul>	<ul style="list-style-type: none"> <li>■ General sealing of color-critical assemblies and components</li> </ul>
SILICONE	BOATLIFE	3M	SIKA ADVANTAGES	SIKA APPLICATIONS
<b>Sikasil® N-Plus</b>	Silicone Rubber	Marine Silicone	<ul style="list-style-type: none"> <li>■ Extremely long service life</li> <li>■ Excellent flexibility</li> <li>■ Available in clear and white</li> <li>■ Bonds to many substrates without primer</li> <li>■ Mildew-resistant</li> </ul>	<ul style="list-style-type: none"> <li>■ Window and door fabrication</li> <li>■ Conventional glazing</li> <li>■ Back bedding</li> <li>■ Cap, toe and heel beads</li> <li>■ Expansion and control joints</li> <li>■ Perimeter sealing of windows &amp; doors</li> <li>■ Kitchen/bath solid surfaces</li> <li>■ Sanitary seals</li> </ul>
2-COMPONENT MMA	BOATLIFE	3M	SIKA ADVANTAGES	SIKA APPLICATIONS
<b>SikaForce®-315</b>	N/A	N/A	<ul style="list-style-type: none"> <li>■ Very fast-setting</li> <li>■ Packaged for precise mixing and easy dispensing</li> </ul>	<ul style="list-style-type: none"> <li>■ Small-component bonding for glass, metals and most plastics</li> </ul>

\*Polysulfide \*\*Polyether



# COMPOSITE REPAIR | COMPETITOR COMPARISON

SIKA TECHNOLOGY	COMPETITORS				SIKA ADVANTAGES	SIKA APPLICATIONS
POLYESTER FILLERS	3M	EVERCOAT	ARJAY	ATC		
SikaBiresin® AP077	Marine Premium Filler	Formula 27 & Marine Filler	1201	Polyfair F26	<ul style="list-style-type: none"> <li>■ Suitable for above &amp; below the waterline applications</li> <li>■ High heat-resistance of 400°F (209°C)</li> <li>■ Bonds to epoxy</li> <li>■ Styrene free</li> </ul>	<ul style="list-style-type: none"> <li>■ Gelcoat repair</li> <li>■ Blister repair</li> <li>■ Repair of damaged fiberglass parts</li> </ul>
SikaBiresin® AP112	Marine High Strength Repair Filler	Kitty Hair & Everglass	3401	N/A	<ul style="list-style-type: none"> <li>■ Fiber-filled</li> <li>■ High impact strength</li> <li>■ Excellent heat and cold resistance</li> <li>■ Can be machined and tapped</li> </ul>	<ul style="list-style-type: none"> <li>■ Structural repairs</li> <li>■ FRP, metal and wood bonding</li> </ul>
EPOXY FAIRING COMPOUND	AWLGRIP	ALEXSEAL	PETTIT		SIKA ADVANTAGES	SIKA APPLICATIONS
SikaBiresin® AP861 (A)	D8200/D7200	Fairing Compound 202	EZ-Fair		<ul style="list-style-type: none"> <li>■ Smoother/creamier aspect</li> <li>■ Less pinholes</li> </ul>	<ul style="list-style-type: none"> <li>■ Fairing large dissimilar material surfaces such as aluminum, steel, FRP and wood</li> </ul>
SikaBiresin® AP861-1 (B)						
EPOXY RESIN SYSTEM	COPOXY*	WEST SYSTEMS*		SIKA ADVANTAGES	SIKA APPLICATIONS	
SikaBiresin® CR72 (A)	100A 4528A	WEST-105		<ul style="list-style-type: none"> <li>■ Higher physical properties*</li> <li>■ Higher thermal properties*</li> <li>■ Less brittle at room temp*</li> <li>■ Improved wet-out*</li> </ul>	<ul style="list-style-type: none"> <li>■ High performance marine boats, parts, and tooling applications</li> <li>■ Suitable for wet layup and vacuum-bagging</li> </ul>	
SikaBiresin® CH72-1 (B)						
SikaBiresin® CH72-2 (B)						
SikaBiresin® CH72-3 (B)						