

ACR RCL-100 LED

12/24V 200,000 CD Searchlight with Optional Wireless Controllers

The RCL-100 LED continues to utilize the same rugged design as the original RCL-100, but incorporates a new efficient 9 LED array that produces over 200,000 candela of light. Other features include a remote control operation that allows users to rotate the light 360 degrees continuously at either a fast or slow speed without the hassle of a hard stop.

With a 7 degree beam angle, the light also provides elevation angles at 9 degrees up and 17 degrees down to make lighting draw bridges, buoys and docks a breeze.

Not all searchlights are created equal. The die cast aluminum case is triple-primed and painted with UV stabilizer to withstand years of exposure in harsh marine environment. The light's internal elevation mechanisms are fully enclosed and provide precise pitch control of the beam while staying protected.

The LED bulbs are efficiently designed to provide over 40,000 operating hours. The light also includes our Exclusive XRCiZ[™] feature that's pre-programmed and allows for the light to independently rotate

every 30 days from activation to insure all bearing surfaces are free of corrosion and all electrical contacts functional.

The RCL-100 LED is completely weatherproof and is available with a weatherproof remote control and operates with 12 or 24 DC power.

Basic Kit / PN 1950: RCL-100 LED Searchlight Only



Wired Kit / PN 1951: RCL-100 LED Searchlight with Master Controller and Wired Point Pad Controller



*Wireless Kit / PN 1952:

RCL-100 LED Searchlight with 4" Tall Wireless Pedestal and Remote Controller



*Mobile Kit / PN 1953:

RCL-100 LED Searchlight with Master Controller, Wi-Fi Remote Control for Mobile Devices, and Wired Point Pad Controller



For further information please contact:

ACR Electronics, Inc. 5757 Ravenswood Road Fort Lauderdale, FL 33312

Tel: (954) 981.3333 Fax: (954) 983.5087 Email: sales@acrartex.com

SPECIFICATIONS

8 x 9 x 8" (20.3 x 22.9 x 20.3 cm) Size

Weight 7 lbs (3.17 kg)

Material Aluminum Alloy Die Casting

Color White

Remote controlled Point Pad Operation (Wireless/Mobile/Wired)

Beam Angle

Elevation 9° up, 17° down Angle

360° continuous Rotation

Rotation Fast 31° per second, slow 20° per

Speed second

Elevation 2.8° per second Speed

High intensity LED (40,000 hour life) Lamp

4.75" (12.1 cm) Light Footprint

8" (20.3 cm) Wireless Pedestal (Kit Diameter

P/N 1952)

Power 12 or 24 V DC

Requirements

Peak Beam Candle Power

200,000





Compatible

with iOS & Android

Devices

*Wireless controllers/wireless controller accessories have not yet received FCC approval. *This device has not yet been authorized as required by the Rules of the FCC. This device is not, and may not be offered for sale or lease, or sold or leased until such authorization is obtained.