



SIONYX

NIGHTWAVE™ D1



MARINE COLOR DIGITAL NIGHT VISION CAMERA

MODEL NO
CRV-500C

Nightwave is an ultra low-light marine navigational camera built around SIONYX's patented Black Silicon CMOS sensor. It allows mariners of all levels to easily spot obstacles and debris in moonless starlight without white light or expensive thermal cameras – navigating safely, avoiding collisions, and maximizing time on the water. With flexible mounting options and easy setup, Nightwave connects to other hardware via analog output, displaying clear color digital night vision.

NIGHTWAVE D1 GRAY
SKU C014700
UPC-A 811251020231

NIGHTWAVE D1 WHITE
SKU C012800
UPC-A 811251020149

NIGHTWAVE D1 BLACK
SKU C014900
UPC-A 811251020248

CONNECTED

Seamless integration with major brand MFDs via the analog video output. Convenient installation flexibility and WiFi communication for command and control.

RUGGED

IP67 rating protects against water, sand, salt, and dust. Dry nitrogen purged to prevent lens fogging. Safely use Nightwave in inclement weather conditions.

CAPABLE

<1 MLX MOONLESS STARLIGHT sensitivity allows you to see well beyond human eyesight.

AWARE

44° field of view increases situational awareness to spot unexpected obstacles, debris, markers, vessels, and more.

CAMERA

SENSOR TYPE	XQE1350 BSI CMOS
RESOLUTION	1280 X 1024
FRAME RATE	30 HZ
HORIZONTAL FOV	44°
VISIBLE SPECTRUM	400-1200NM
FOCUS RANGE	10M TO INFINITY
LENS	16MM F/1.4

SYSTEM

VIDEO OUT	NTSC (640 X 480 @ 30 HZ)
VIDEO CONNECTION	SMA / BNC/ RCA
WIRELESS COMMUNICATIONS	WIFI + BLUETOOTH
POWER IN	12V DC
POWER CONNECTION	TINNED COPPER WIRE

ENVIRONMENTAL

INGRESS PROTECTION	IP67 WATER/DUST RESISTANT
SHOCK & VIBRATION	IEC60945 [V15G H:9G] IK08
OPERATING TEMPERATURE	-20°C TO +50°C
STORAGE TEMPERATURE	-20°C TO +80°C

RANGE PERFORMANCE

	CLEAR WEATHER AT 1/4 MOON
DETECT MAN-SIZED OBJECT	150 M

All product, product specification, and data are subject to change without notice to improve reliability, function, design, or otherwise. Visit SIONYX.COM for up-to-date documentation.


CAMERA - PHYSICAL

WEIGHT	870 G [1.9 LBS]
DIMENSIONS	127 X 127 X 152 MM [5 X 5 X 6 IN]
MOUNTING OPTIONS	TRIPOD OR RAMMOUNT SINGLE 1/4" 20 CENTER MOUNT BULKHEAD MOUNT: 4 X M6 BLIND HOLES TOP-DOWN MOUNTING HOLES
MATERIAL	UV RESISTANT POLYCARBONATE

INCLUDED

CAMERA	DIGITAL VIDEO CABLE USB
CABLE [5M]	BASE GASKET
SMA TO BNC ADAPTER	MOUNTING HARDWARE
BNC TO RCA ADAPTER	INSTALL TEMPLATE
POWER FUSE & FUSE HOLDER	USER MANUAL

EYESIGHT VS NIGHTWAVE



SIONYX.COM | info@sionyx.com | (978) 922-0684
100 Cummings Center | Suite 303B | Beverly, MA 01915 | USA

Get connected with the SIONYX Mobile App

