



ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	ADASTLKA	STARLINK MARITIME TOP PLATE	1
2	ADAGMT	RUBBER GROMMET	1
3	51618114FHCS	5/16"-18 X 1.25" S.S. FLAT HEAD BOLT	8
4	51618NUT	5/16" S.S. NYLOC NUT	4
5	515NW	5/16" NYLON WASHER	8
6	51618112BHCS	5/16"-18 X 1.5" S.S. BUTTON HEAD BOLT	4
7	516SSW	5/16" S.S. WASHER	4

- BOLT THE TOP PLATE (1) TO THE SEAVIEW MODULAR MOUNT USING THE 8 BOLTS (3). MAKE SURE THE MODULAR TOP GASKET IS ALIGNED IN THE MODULAR TOP GROOVE. THE GASKET SITS BETWEEN THE MOUNT AND THE TOP PLATE.
- PASS YOUR STARLINK CABLE THROUGH THE RUBBER GROMMET (2), THEN RUN IT ALL THE WAY THROUGH THE TOP PLATE AND MOUNT.
- ALIGN THE GROMMET (2) TO THE LIP IN THE CENTER OF THE PLATE (1). MAKE SURE THE GROOVE IN THE GROMMET IS SECURELY WRAPPED AROUND THE PLATE LIP.
- BOLT THE STARLINK WEDGE BASE TO THE TOP PLATE (1) USING THE 4 BOLTS PROVIDED (6). THE BOLTS ARE INSTALLED FROM THE BOTTOM UP TRAVELING FIRST THROUGH THE S.S. WASHERS (7), THEN THE TOP PLATE (1), THE STARLINK WEDGE BASE PLATE, THE PLASTIC WASHERS (5), AND FINALLY INTO THE NYLOC NUTS (4).

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEAVIEW. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEAVIEW IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	 TITLE: <h1>ADASTLKA</h1>	
DIMENSIONS ARE IN INCHES		DRAWN	S.C.		1.13.23
TOLERANCES:		CHECKED			
FRACTIONAL ±		ENG APPR.			
ANGULAR: MACH ± BEND ±		MFG APPR.			
TWO PLACE DECIMAL ±.01		Q.A.			
THREE PLACE DECIMAL ±.003		COMMENTS:			
INTERPRET GEOMETRIC TOLERANCING PER:					
MATERIAL		--		SIZE B DWG. NO. -- REV D	
FINISH		--		SCALE: 1:2 WEIGHT: SHEET 1 OF 1	
NEXT ASSY	USED ON				
APPLICATION		DO NOT SCALE DRAWING			