

THE ORIGINAL
FATSAC
 BALLAST BAG CO.

Barefoot International & Fly High Mfg.
 3879 North Richards Street
 Milwaukee, WI 53212

PHONE 414-964-3668 ■ FAX 414-964-5767 ■ E-MAIL orders@fatsac.com ■ WEB www.fatsac.com



| PART# | DESCRIPTION | • Fittings made for automatic ballast systems |
|---------------|--|---|
| W730 | FEMALE QUICK CONNECT W/CHAIN & CAP — SAC VALVE THREADS | |
| W739 | QUICK CONNECT CAP | |
| W731 | FAT SAC PLUGS — SAC VALVE THREADS | |
| W732 | FEMALE GHT — MALE QUICK CONNECT | |
| W733-SS • | 1" BARBED END — SAC VALVE THREADS — SHOULD USE PERMANENT EPOXY CEMENT (W720) | |
| W734 | MALE QUICK CONNECT — TSUNAMI PUMP THREAD | |
| W735 | FEMALE QUICK CONNECT — BLUE PERFECT UNION FITTING | |
| W736-SS • | 3/4" QUICK CONNECT — SAC VALVE THREADS — SHOULD USE PERMANENT EPOXY CEMENT (W720) | |
| W737 • | 3/4" BARBED END — SAC VALVE THREADS — SHOULD USE PERMANENT EPOXY CEMENT (W720) | |
| W738 | MALE QUICK CONNECT — 1-1/8" BARBED TSUNAMI PUMP HOSE END | |
| W740 • | FLOW-RITE 3/4" STRAIGHT QUICK CONNECT SOCKET | |
| W741 • | FLOW-RITE 1-1/8" STRAIGHT QUICK CONNECT SOCKET | |
| W742 • | FLOW-RITE 3/4" ELBOW QUICK CONNECT SOCKET | |
| W746 • | FLOW-RITE 1-1/8" ELBOW QUICK CONNECT SOCKET | |
| W746-PLUG • | FLOW-RITE 1-1/8" PLUG FITS INSIDE W746/W741 FITTINGS TO CAP OFF PNP SYSTEMS IN BOATS — COMES WITH DOUBLE O-RINGS FOR BEST SEAL | |
| W743-DOUBLE • | DOUBLE SIDED 1-1/8" QUICK CONNECT FITTING | |
| W743-SS • | SUCTION STOP SAC VALVE THREADS — 1-1/8" QUICK CONNECT — SHOULD USE PERMANENT EPOXY CEMENT (W720) | |
| W744 | PRO X SERIES CHECK VALVE — ALL CHECK VALVES SLIGHTLY HINDER FLOW | |
| W745 • | 3/4" BARBED TSUNAMI PUMP FITTING | |
| W747 • | SAC VALVE THREAD FOR TSUNAMI PUMP — SHOULD USE PERMANENT EPOXY CEMENT (W720) | |
| W748 • | 1-1/8" QUICK CONNECT TO 1" BARBED | |
| W749 | AIR RELEASE PLUG — TURN TO RELEASE AIR. FOR MANUAL FILLING, NOT FOR VENTING AUTOMATIC SYSTEMS. | |
| W753 • | 1" BARBED IN-LINE CHECK VALVE | |
| W755 • | 1-1/8" BARBED IN-LINE CHECK VALVE | |
| W766 | SUPA PUMP ZURU BALLOON ADAPTER ACCESSORY | |
| W720 | EPOXY CEMENT FOR FITTINGS, 25ML OR 1 OZ TUBES (AKA:50805) — MIX WELL BEFORE USE! | |

NOTE: There are many possible combinations using our Quick Connect fittings. If you are trying to accomplish something and aren't sure how to best handle it, please contact us and we will be glad to help.

IMPORTANT: Use All-Purpose PVC Cement on the threads of the W733-SS, W736-SS, W737, W743-SS, and W747 when screwing them into Fat Sacs.